


额定电压 Rated voltage	AC250V 50Hz/60Hz	
额定电流 Rated current	10A (电阻负载 resistive load)	
接点形式 Contacts	单刀单掷, 自动复位 SPST, auto-reset	
动作温度 Operating temperature	断开 OFF: 105±5.0°C (open)	接通 ON: 88±7.0°C (close)
绝缘外壳材质 Material of base	陶瓷 ceramic	
感温盖材质 Material of sensing cover	铝 aluminum	
接线端子材质 Material of termina	锌白铜 packfong	
绝缘电阻 Insulation Resistance	10MW以上 (DC 500V 兆欧表, 冷态) More than 10MW (with DC 500V megger)	
接触电阻 Contact Resistance	≤50m Ω	
使用寿命 Life(resistive load)	超过 100,000 次 more than 100,000 cycles;	
认证 Approved	CQC/TUV	
标记系列号 Marking series no.	KSD309-A (激光打标或钢模压印 Laser marking or tool impression)	
客户的物料代号 Client's PN		

请贵司在本图签名确认。若贵司不签名确认而直接下单, 我司将视贵司已经确认本图纸。
Customer should sign and stamp on this drawing before placing orders. If customer place orders without sign and stamp, we will consider customer has confirmed this drawing.

 未注公差: ±0.5mm Undeclared tolerance: ±0.5mm	标题 Title:	图号 Drawing no.:	版本 REV.:
	突跳式温控器 Snap-Action Thermostat	CS210755	A
单位 Unit: mm	比例 Scale: 2 : 1	ERP编号 ERP no.:	
幅面 Size: A3			
共1页 第1页			
出图 Drawn by	洗崇礼	产品型号或材料规格 Type of product or spec. of material:	
审核 Checked by		KSD309-10.5/10LC15-AY45	
日期 Date	2021-8-26	 东莞市天瑞电子有限公司 DONGGUAN TIANRUI ELECTRONICS CO., LTD.	